



HYPER TURBO HT-777 Owners Manual

Specifications:

- Designed for cleaning hard surfaces with your truckmount or high pressure portable
- Standard Brush Ring
- Stainless steel Handle with High Temp Powder Coated Stainless Steel Deck.
- Operating pressure range up to 2500psi (HT-777LP) to 4000psi (HT-777HP).
- Water temp. up to 230° (HT-777LP) or 250° (HT-777HP).
- Comfort grip non-slip handle
- *Patented automatic vacuum compensator leaves the floor drier.*
- Easy access inline filter.

Limitation of Liability

Turbo Force International's (T.F.I.) liability on any claim for loss or damage connected with the supplying of goods, or their sale, resale, operation, or use, warranty, tort (including negligence) or other grounds, shall not exceed the price allowable to such goods or part thereof involved in any claim.

T.F.I. shall not under any circumstances be liable for any labor charges, special or consequential damages including, but not limited to, bodily injury, loss of profits or revenues, loss of use of any product or associated product, cost of capital, cost of substitute products, facilities or services, downtime costs or costs of claims arising from Buyer or Buyer's customers.

Any technical advice or assistance furnished by Turbo Force International which concerns any goods supplied hereunder, will not subject T.F.I. to any liability, whether based on contract, warranty, tort (including negligence) or other grounds

***DO NOT PUT YOUR HANDS UNDER THE DECK WHILE THE TOOL IS IN USE AND AFTER THE TRIGGER HANDLE IS RELEASED (WAIT 2 MINUTES FOR THE SPRAY BAR TO COMPLETELY STOP), FAILURE TO DO SO CAN CAUSE SERIOUS INJURY AND TURBO FORCE INTERNATIONAL WILL NOT BE HELD LIABLE FOR DISREGARDING THIS WARNING WHICH RESULTS IN ANY BUT NOT LIMITED TO INJURIES, DAMAGE, LOSS OF LIMBS AND OR LIFE.**

Warranty:


Turbo-Force International warrants that its product(s) (the Product) shall be free from defects in materials and workmanship under normal use, installation and maintenance in accordance with T.F.I. specifications for a period of 1 year from the date of purchase. If any failure to conform to this warranty is reported to T.F.I. within 1 year from the date of purchase by the original buyer, T.F.I., upon being satisfied of the existence of such non-conformity, will, with exclusions (wear and tear) etc., correct same at its discretion by repairing or replacing the Product.

Exclusions: The swivel (T-8a) is a sealed item it will not be covered if factory seal is broken from improper adjustment or installation. Swivel must be returned to T.F.I. for evaluation. Swivel will be repaired or replaced at manufacturer's discretion. Swivels that show signs of abuse or misuse will not be warranted. Interface ring or "boot" is covered from breakage or defect only for 90 days; there is no warranty against wear. Vacuum hoses, high pressure lines, and fittings are not covered under this warranty.

This warranty does not cover damage resulting from mishandling in transit, vandalism, misuse, abuse, neglect, alteration, dismantling, excess heat, acts of God or failure to exercise reasonable care in using or maintaining the Product. This warranty applies only to the original purchaser / owner of the Product. Original sales receipt / sales contract is required to validate warranty. To obtain service under this warranty, contact your dealer.

This warranty is in lieu of and excludes all other warranties, express or implied, arising by operation of law or otherwise, including any warranty of merchantability or fitness for particular purpose or otherwise, and no representation of warranty, expressed or implied, made by any sales representative or other agent of T.F.I. In no event shall T.F.I. be liable for incidental or consequential damages.

This warranty gives you specific legal rights which may vary from state to state.



TH-V10
Vacuum Slide

TH-140
24" Steel Coil
Vac Hose

TH-48HP
Steel Braided
Hose

O RING*

HT-Deck
Bolts

Low Pressure Swivel
T-8a

High Pressure Swivel
HT-4000

HT-CASTERS

HT-BRUSH

DECK DISASSEMBLY

1. Remove HP Line with 9/16 wrench
2. Remove swivel
3. Remove all 8 bolts with 1/2 socket for the nuts and 9/16 wrench for the bolts
4. When reassembling unit make sure you put the **ORING** back around the compensator between the inner and outer deck.

